

# RUNDO ROUND



LIGHT·POINT

## Technical specification

Family luminaire for indoor use. For wall/ceiling mounting and suspension and with direct/indirect light or direct light only. Available in three colours white, black and silver. With built in electronic gear. For LED or T16 and low energy light sources.

## Technical data

Material	Aluminum
Diffuser	Acryl opal diffuser
Colour	White (.W), Black (.B), Silver (.S) <b>PLEASE AD COLOUR TO CODE</b>
Light Source	T16, TC-L and LED MacAdam 3
Voltage	230-240 V
Control gear	Electronic
Color temperature	3000 or 4000 K
CRI (Ra)	80>



## NOTE:

Light source must be ordered separately. LED luminaire is with light source.

It is necessary to order assembly kits 13-0002 or 13-0004 for pendant installation

It is necessary to order assembly kit 19-0008 for distance between mounting surface and luminaire.


The luminaire is available on request for DALI (...D), analog 1-10V (...A) or switch (...T) dimming.

The luminaire is available on request for emergency; 1 hour (...M) or 3 hour (...M3).

## RUNDO DIRECT/INDIRECT LIGHT




CODE	MEASURE mm	LIGHT SOURCE	MOUNTING
19-551K-1V1UE..	Ø370XH70	1x22W 2GX13+1x40W 2GX13	Wall, ceiling and suspension
19-551K-1040E..	Ø370XH70	1x40W 2GX13	Wall, ceiling and suspension
19-551K-1055E..	Ø370 XH70	1x55W 2GX13	Wall, ceiling and suspension
19-551K-1U1WE..	Ø450 XH70	1x22W 2GX13+1x60W 2GX13	Wall, ceiling and suspension
19-551K-1060E..	Ø450XH70	1x60W 2GX13	Wall, ceiling and suspension
19-561K-4E2JE..	Ø650XH70	4x24W T16+2x24W 2G11	Wall, ceiling and suspension




## RUNDO DIRECT LIGHT ONLY




CODE	MEASURE mm	LIGHT SOURCE	MOUNTING
19-250K-1V1UE..	Ø370XH70	1x22W 2GX13+1x40W 2GX13	Wall, ceiling and suspension
19-250K-1040E..	Ø370XH70	1x40W 2GX13	Wall, ceiling and suspension
19-250K-1055E..	Ø370XH70	1x55W 2GX13	Wall, ceiling and suspension
19-250K-1U1WE..	Ø450XH70	1x22W 2GX13+1x60W 2GX13	Wall, ceiling and suspension
19-250K-1060E..	Ø450XH70	1x60W 2GX13	Wall, ceiling and suspension
19-260K-4E2JE..	Ø650XH70	4x24W T16+2x24W 2G11	Wall, ceiling and suspension



# RUNDO DIRECT LIGHT ONLY LED



CODE	MEASURE mm	LIGHT SOURCE	TOTAL FLUX (lm)	MOUNTING
19-243K-10GEE/830..	Ø250XH70	LED 1X15W	1010 lm	Wall/ceiling and suspension
19-243K-10GEE/840..	Ø250XH70	LED 1X15W	1010 lm	Wall/ceiling and suspension
19-252K-10GHE/830..	Ø370XH70	LED 1X20W	1620 lm	Wall/ceiling and suspension
19-252K-10GHE/840..	Ø370XH70	LED 1X20W	1620 lm	Wall/ceiling and suspension
19-252K-10GIE/830..	Ø450XH70	LED 1X30W	2440 lm	Wall/ceiling and suspension
19-252K-10GIE/840..	Ø450XH70	LED 1X30W	2650 lm	Wall/ceiling and suspension
19-262K-10GNE/830..	Ø650XH70	LED 1x66W	5260 lm	Wall/ceiling and suspension
19-262K-10GNE/840..	Ø650XH70	LED 1x66W	5710 lm	Wall/ceiling and suspension



## ACCESSORIES – RUNDO ROUND DIRECT/INDIRECT and DIRECT LIGHT

CODE	DESCRIPTION	DRAWING	+ PICTURE
19-0008..	Accessory for creating of distance between mounting surface and luminaire, for circular luminaire with Ø 450 mm, Ø 650 mm <b>FOR RUNDO DIRECT/INDIRECT ONLY</b>		
13-0002..	Wire suspension 2000 mm, 3 wires, ceiling cup, transparent cable 4x 0.75 mm, 2000 mm <b>FOR RUNDO DIRECT/INDIRECT and DIRECT LIGHT</b>		
13-0004..	Wire suspension 2000 mm, 3 wires, ceiling cup, transparent cable 5x 0.75 mm, 2000 mm <b>FOR RUNDO DIRECT/INDIRECT and DIRECT LIGHT</b>		
19.0009..	Accessory for creating of distance between mounting surface and luminaire, for square luminaires and circular luminaire with Ø 370 mm		



### LIGHT-POINT AS

Gothersgade 14  
DK-1123 Copenhagen K

T +45 7025 5525  
F +45 7025 6625

[www.light-point.dk](http://www.light-point.dk)  
[info@light-point.dk](mailto:info@light-point.dk)

Danske Bank 3191 0003415813  
IBAN DK343000003415813